

F25188

F25223

F25830


General-Duty Polypropylene Caster

Polypropylene caster, rigid or swiveling, available with or without break



Advantages and benefits

- Non-marking tread.
- Light, economical, and impact-resistant; does not absorb water or chemical products.
- Corrosion-resistant zinc finish.

Conditions:

- *Water: Optimal*
- *Solvents: Optimal*
- *Detergents: Optimal*
- *Acids: Optimal*
- *Extreme cold: Not recommended*
- *Extreme heat : Not recommended*
- *Petroleum products: Optimal*

Recommended surfaces:



Product number	Description	Wheel Diameter	Load Capacity	Tread Width	Overall Height
F25190	50mm Swiveling caster	50mm (2")	57 kg (126lbs)	20mm (3/4")	62mm (2-7/16")
F25232	50mm Swiveling caster w/break	50mm (2")	57 kg (126lbs)	20mm (3/4")	62mm (2-7/16")
F25827	50mm Rigid caster	50mm (2")	57 kg (126lbs)	20mm (3/4")	62mm (2-7/16")
F25188	61mm Swiveling caster	61mm (2-3/8")	80 kg (176lbs)	29mm (1-1/8")	81mm (3-3/16")
F25233	63mm Swiveling caster w/break	63mm (2-1/2")	80 kg (176lbs)	32mm (1-1/4")	82mm (3-1/4")
F25828	63mm Rigid caster	63mm (2-1/2")	80 kg (176lbs)	29mm (1-1/8")	81mm (3-3/16")
F25189	75mm Swiveling caster	75mm (3")	91 kg (201lbs)	32mm (1-1/4")	97mm (3-3/4")
F25234	76mm Swiveling caster w/break	76mm (3")	123 kg (270lbs)	32mm (1-1/4")	97mm (3-3/4")
F25829	76mm Rigid caster	76mm (3")	123 kg (270lbs)	32mm (1-1/4")	97mm (3-3/4")
F25191	100mm Swiveling caster	100mm (4")	116 kg (256lbs)	32mm (1-1/4")	125mm (5")
F25223	102mm Swiveling caster w/break	102mm (4")	159 kg (350lbs)	33mm (1-5/16")	127mm (5")
F25830	102mm Rigid caster	102mm (4")	159 kg (350lbs)	33mm (1-5/16")	127mm (5")